<sup>a</sup>Erodibility factors:

Mack loam

**Soil Name** 

Ravola

Toddler

Glenton

Table 3–30. Soil Types and Properties at the Crescent Junction Site

Permeability

(inches per hour)

0.2 - 6.0

0.6-2.0

2.0-6.0

0.2 - 6.0

Available Water

(percent)

10-18

10-18

8-18

12 – 19

Textural

Class

Silt loam to

fine sandy

Silt loam to

fine sandy

Silt loam to

fine sandy

loam

loam

loam

Silt loam

Clay

(percent)

15–35

18-35

5-18

5 – 19

**Erodibility** 

Factors<sup>a</sup>

K = 0.43

K = 0.32

Wind = 4

K = 0.24

Wind = 3

K = 0.32

Wind = 4L

T = 5

T = 5Wind = 4

T = 5

T = 5

Salinity

(mmho/cm)

4-16

2–8

< 8

<2-4

K, used in the Universal Soil Loss Equation, is an indicator of the susceptibility of a soil to sheet and rill erosion by water. Values range from 0.02 to 0.69; the higher the value, the more susceptible the soil is to sheet and rill erosion.

T is an estimate of the maximum average annual rate of water or wind erosion in tons per acre per year.

Depth

(inches)

> 60

> 60

> 60

> 60

**Taxonomy** 

(calcareous), mesic

(calcareous), mesic

Typic Torrifluvents

mixed (calcareous),

Fine-loamy, mixed,

Typic Torrifluvents

Fine-silty, mixed

Coarse-loamy,

mesic Typic

Torrifluvents

mesic typic

Haplargids

Fine-silty, mixed

Wind erosion factors range from 1 to 8; the lower the value, the more susceptible the soil is to wind erosion. mmho/cm = millimhos per centimeter.

рН

7.9-9.0

7.9-9.0

7.9-8.4

7.4-9.0

Source: SCS 1989.